

AGROTRON M

	M 410	M 420	M 600	M 610	M 615	M 620	M 625	M 640	M 650	
Motor										
Motor diesel TCD Deutz cu racire cu apa	Tip	2012 L04 4V		2012 L06 2V		2012 L06 4V		2012 L06 2V		2012 L06 4V
Cilindri/Cilindree	nr/cm ³	4/4038						6/6057		
Alezaj/Cursa	mm									101/126
Sistem de injectie DCR (Detz Common Rail) cu presinute de injectie 1600 bar										
Putere nominala	CP/kW	98/134	113/154	89/121	97/132	107/146	114/155	120/163	125/171	133/181
Putere max omologata(2000/25/CE)	CP/kW	98/134	113/154	97/132	107/146	107/146	120/163	120/163	129/176	135/184
Putere max cu DPC	CP/kW	104/142	116/157	97/132	107/146	110/149	122/166	122/166	133/181	141/192
Regim nominal	rot/min			2100						
Cuplu max	Nm	610	659	599	599	599	659	659	717	749
Regim cuplu max	rot/min	1600-1100		1600-1200		1700-1100		1700-1400		1600-1100
Putere maxima	CP/kW	90/122	97/131	88/120	96/131	98/133	110/149	102/139	120/163	126/171
Regim nominal	rot/min	1600-2100		1700-2100		1800-2100				1750-2100
Aspiratie		Sub capota				Pe montantul lateral, in stanga				Sub capota
Capacitate rezervor	l			270						305
Intervale pentru schimb ulei		12/500 h sau anual				14/500 h sau anual				16/500 h sau anual
Cabina										
Cabina clasa S										Integrata, insonorizata
Nivel sonor	dB (A)									70-73
Brat multifunctional										Standard
Climatizare										Standard
Suspensii										Mecanice sau pneumatice, la cerere
Instalatie electrica										
Tensiune	V									12
Demaror	V/kW									12/4
Baterie	V/A									12/180
Sasiu, frane, directie										
Punte fata										Cuplare centralizata
Suspensii punte fata	50 km/h									Standard
Suspensii punte fata	40 km/h									La cerere
Blocare diferential fata/spate	ASM									Comanda automata in functie de unghiul de virare, viteza, franarea independenta si patinare (valoarea blocarii 100%) dezactivare posibila
Frana	AV/AR									Frana automata/cu discuri in baie de ulei
Raza de viraj	m	4,65		4,95			5,13			5,80
Directie										Load Sensing cu pompa independenta (42 l/180 bar)
Sistem hidraulic										
Sistem										Cu centru deschis sau Load Sensing, la cerere
Debit pompa	l/min(bar)									Cu centru deschis 83 (200)/Load Sensing 120 (200)
PTO fata (optional)										
Ambreiaj										
Comanda/Sens										Electrohidraulica/dreapta
Regim motor la 1960 rot/min	rot/min									1000
PTO spate										
Ambreiaj										In baie de ulei, demarare modulata
Comanda										Comanda electrohidraulica, functionare automata
Regim motor 540/1000 si 540E/1000E	rot/min									1995 si 1610 rot/min
Transmisie										
Tip de transmisie										7200; 6 game viteze; sincronizata
Inversor Powershuttle										Serie
Viteza max	km/h									Limitat la 40/50 km/h in regim economic al motorului
Ambreiaj										Cu discuri in baie de ulei
Ridicator spate										
Agrotronic-hD										Control: Forta/Pozitie/Mixt/Flotant/Diagnoza/Patinaj/Compensare oscilatii
Capacitate de ridicare	kg									9200
Dimensiuni										
Ampatament	mm	2419				2647		2767		2817
Lungime	mm	4359				4587		4757		4807
Inaltime la cabina	mm	3004	3054	3004		3054		3007		3127
Latime totala	mm			2540						2720
Lumina	mm			520				570		605
Greutate tot autoriz 40 km/h	kg	9500	10300	9500		10300		11000	11850	
Greutate tot autoriz 50 km/h	kg	8500	9000	8500		9000		10000	11000	

Caracteristicile mai sus mentionate se refera la dotarea cea mai completa disponibila. In ceea ce priveste accesoriile si dotarile, utilizati lista de preturi in vigoare.

AGRIROMEX

Str. Lt. Av. Gheorghe Negel nr. 29
Sector 6, Bucuresti
Tel: 021 316 01 65
Fax: 021 316 01 94

