

USCATOR MOBIL FSN

- Pot fi actionate la priza de forta a tractorului sau de un motor electric
- Combustibilul utilizat poate fi motorina sau gaz



Model	Capacit	Timp Incarc	Capacitate evaporare	Timp descarc	Timp uscare de la 20 la 15%	Timp uscare de la 25 la 15 %	Timp Racire	prod. zilnica de la 20 al 15% produs verde racit	prod. zilnica de la 25 al 15% produs verde racit	prod. zilnica de la 20 al 15% produs verde fara racire	prod. zilnica de la 25 al 15% produs verde fara racire
	mc-t	h	Puncte/h	h	h	h	h	mc/zi	mc/zi	mc/zi	mc/zi
FSN 11/103 F	15 10,9	0,19	5	0,19	1,0	2,0	1,0	147	103	254	147
FSN 12/110 F	16 11,7	0,20	5	0,20	1,0	2,0	1,0	156	110	267	156
FSN 13/127 T	18 13,7	0,23	5	0,23	1,0	2,0	1,0	178	127	299	178
FSN 15/138 T	20 15,2	0,26	5	0,26	1,0	2,0	1,0	193	138	320	193
FSN 15/138 T2	20 15,2	0,26	5	0,26	1,0	2,0	1,0	193	138	319	193

AGRIROMEX

Splaiul Independentei nr. 17
Sector 5, Bucuresti
Tel: 021 316 01 65
Fax: 021 316 01 94

MECMAR
TECNOLOGIE PER LA CONSERVAZIONE