

INFASURATOR BALOTI

INCARCAREA BALOTULUI SE FACE DIN SPATE



Model		G400P	G400F	G400S
LUNGIME TOTALA	(cm)	285	285	400
LATIME DE TRANSPORT	(cm)	162	187	193
LUNGIME TOTALA(DE LUCRU)	(cm)	170	190	190
INALTIME(LA NIV. ROLELOR)	(cm)	65	83	83
GREUTATE	(kg)	750	860	850
MARIME ROTI		-	20x10.0-10	20x10.0-10
CAP. DE INC. A BRATULUI RIDICATOR	(kg)	-	1000	1000
CONECTARE HIDRAULICA	(nr.)	1DA	1DA	1DA
DEBIT POMPA HIDRAULICA TRACTOR(VIT. MAX A PLATFORMEI LA 25 R.P.M.)		23	23	23
CONECTARE LA TRACTOR		3 pct(cat I si II)	3 pct(cat I si II)	Inel de prindere Ø35
DIMENSIUNI BALOTI	(cm)	Ø120-160 max W.130	Ø120-160 max W.130	Ø120-160 max W.130
GREUTATE MAX BALOTI	(kg)	1000	1000	1000
STRATURI FOLIE	(nr.)	2-3-2+2-3+3	2-3-2+2-3+3	2-3-2+2-3+3
GROSIME FOLIE	(micron)	25-35	25-35	25-35
DIMENSIUNI BOBINE FOLIE-HxØ	(mm)	500/750/280	500/750/280	500/750/280
Echipment		G400P	G400F	G400S
ROTI 20x10.00-10-PT VARIANTELE S SI F		NU	STD	STD
PLATFORMA CU 3 CURELE		STD	STD	STD
DISPOZITIV DE TAIERE AUTOM A FOLIEI		STD	STD	STD
ROLA GHIDARE FOLIE		STD	STD	STD
SELECTIE SUPRAPUNERE FOLIE		STD	STD	STD
4 SELECTII PRE-TENSIONARE FOLIE		STD	STD	STD
PROTECTIE CIRCUIT HIDRAULIC (ANTI-SOC)		STD	STD	STD
RACORDURI HIDRAULICE CU PRINDERE RAPIDA		STD	STD	STD
DISPOZITIV PRE-TENSIONARE PT BOBINE 750/500 MM		STD	STD	STD
PLATFORMA CU 2 ROLE		STD	STD	STD
BRAT DE INCARCARE-DESCARCARE POSTERIOR (VERSIUNILE S SI F)		NU	STD	STD
CADRU SOLID PT BALOTI DE PANA LA1000KG		STD	STD	STD

AGRIROMEX

Splaiul Independentei nr. 17
Sector 5, Bucuresti
Tel: 021 316 01 65
Fax: 021 316 01 94



INFASURATOR BALOTI

INCARCAREA BALOTULUI SE FACE DIN LATERAL



Model	G600S	
LUNGIME TOTALA	(cm)	432
LATIME DE TRANSPORT	(cm)	252
INALTIME(la nivelul rolor)	(cm)	110
INALTIME TOTALA(de lucru)	(cm)	234
GREUTATE	(kg)	1080
MARIME ROTI		10.0/80-12
CONECTARE HIDRAULICA	(nr.)	1DA
DEBIT POMPA HIDRAULICA TRACTOR(VIT MAX A PLATFORMEI LA 25 R.P.M.)		23
CONECTARE LA TRACTOR		Inel de prindere Ø35
DIMENSIUNI BALOTI	(cm)	Ø120-160
GREUTATE MAX BALOTI	(kg)	1000
STRATURI FOLIE	(nr.)	2-3-2+2-3+3
GROSIME FOLIE	(micron)	25-35
DIMENSIUNI BOBINE FILM-HxØ	(mm)	500/750x280
Echipament	G600S	
PLATFORMA CU 2 ROLE SI 4 CURELE		STD
CADRU SOLID PENTRU BALOTI DE PANA LA 1000 KG		STD
PLATFORMA CU 4 CURELE		STD
PLATFORMA CU 2 ROLE		STD
DISPOZITIV DE TAIERE AUTOMATA A FOLIEI		STD
SELECTIE SUPRAPUNERE FOLIE		STD
4 SELECTII PRE-TENSIONARE FOLIE		STD
DISPOZITIV PRE-TENSIONARE PT BOBINE 750/500 MM		STD
ROLA GHIDARE FOLIE		STD
PROTECTIE CIRCUIT HIDRAULIC(ANTI-SOC)		STD
RACORDURI HIDRAULICE CU PRINDERE RAPIDA		STD
ROTI:10.0/80-12		STD
COMANDA LA DISTANTA CABLU		STD
CONTOR DE TURATIE ELECTRONIC		STD

AGRIROMEX

Splaiul Independentei nr. 17
Sector 5, Bucuresti
Tel: 021 316 01 65
Fax: 021 316 01 94

