

USCATOR MOBIL SSI

- Pot fi actionate la priza de forta a tractorului sau de un motor electric
- Combustibilul utilizat poate fi motorina sau gaz



Model	Capacit	Timp Incarc	Capacitate evaporare	Timp descarc	Timp uscare de la 20 la 15%	Timp uscare de la 25 la 15 %	Timp Racire	prod. zilnica de la 20 al 15% produs verde racit	prod. zilnica de la 25 al 15% produs verde racit	prod. zilnica de la 20 al 15% produs verde fara racire	prod. zilnica de la 25 al 15% produs verde fara racire
	mc-t	h	Puncte/h	h	h	h	h	mc/zi	mc/zi	mc/zi	mc/zi
SSI 18/164 T	25 18,6	0,32	5	0,32	1,0	2,0	1,0	226	164	364	226
SSI 20/171 T	26 19,7	0,34	5	0,34	1,0	2,0	1,0	235	171	376	235
SSI 24/203 T2	33 24,4	0,42	5	0,42	1,0	2,0	1,0	275	203	425	275
SSI 25/210 T2	34 25,4	0,43	5	0,43	1,0	2,0	1,0	284	210	435	284

AGRIROMEX

Splaiul Independentei nr. 17
Sector 5, Bucuresti
Tel: 021 316 01 65
Fax: 021 316 01 94

MECMAR
TECNOLOGIE PER LA CONSERVAZIONE